

PRODUCT DATA SHEET

B1500X 100% ACRYLIC PRIMER

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product name **INSULTEC – B1500X Acrylic Primer**

Supplier Insultec (Aust) Pty Ltd
7/24 Garling Road, Kings Park,
New South Wales - 2148 Australia
Telephone: +61 2 9676 5143

Emergency telephone number
Australia +61419296183

Distributor Greentech Building Solutions Pty Ltd
Bay Office 96 Carlton Tce
Manly QLD - 4179 Australia
Telephone: 1300 360 346

DESCRIPTION

B1500X Primer is suitable for a wide variety of substrates such as: Concrete, Gyprock, Brick, Fibro or Slate surfaces and will act as a sealer primer over Bitumen surfaces.

COMPOSITION

B1500X Primer is a water based co-polymer compound containing inert pigments and special fillers.

PROPERTIES

Coverage: One litre per 8 square meters of flat area, assuming no losses.

Drying time: At 25°C. touch one hour, Recoat 4 hours.

Component: One component system.

Shelf life: One year in sealed containers at temperatures of 25°C.

Solids by Vol: 45% +/- one.

No. of coats: One.

Finish: Matt.

Thinners: Water.

Clean up: Water when wet, when dry White Spirits or Turps.

STORAGE

Protect from heat or frost. Ideal storage conditions are in the shade at ambient temperatures of between 10°C and 25°C.

APPLICATION DATA

Stir thoroughly before use, B1500X Primer can be applied by roller, brush or airless spray. Equipment may be cleaned with water and dry paint can be removed with White Spirits or Mineral Turps.

PRECAUTIONS

Provide adequate ventilation during use. Spray painters should comply health regulations. Do not use on glazed surfaces unless previously treated. Do not apply if rain is expected within four hours of finishing painting, or the relative humidity is above 85% or within 3°C of the dew point.

SURFACE PREPARATION

Prepare surfaces as for normal painting,

RESISTANCE

Chemicals: Standard 10% solution of acids and alkalis, impervious to salt spray.

DISCLAIMER

The data contained herein is based upon information which the company believed to be reliable at the time of preparation of this data sheet. No responsibility can be accepted, or any express or implied warranty given where performance of the product is affected by surface preparation, method of application or any other circumstances beyond the control of the company.